

VALVE TRAIN ACCESSORIES

VALVE SPRING SEATS

Part Number	O/D	Spigot Diam.	Bore	Thickness	Part Number	O/D	Spigot Diam.	Bore	Thickness
VSS1128	1.270"	.600"	0.52"	.060"	VSS1251	1.28"	.670"	0.50"	.050"
VSS1258	1.28"	.880"	0.50"	.060"	VSS1451	1.44"	1.085"	0.50"	.095"
VSS1452	1.44"	.792"	0.51"	.060"	VSS1456	1.44"	.792"	0.56"	.050"

VALVE SPRING SHIMS Marked Shims Available In .060"(A) .030"(B) And .015"(C) Thick.

Part Number	O.D.	I.D.	Part Number	O.D.	I.D.	Part Number	O.D.	I.D.
VS250 (A,B,C)	1.250"	0.500"	VS306 (B)	1.440"	0.640"	VS510 (A,B,C)	1.510"	0.570"
VS203 (A,B)	1.250"	0.805"	VS305 (B,C)	1.440"	0.780"	VS740 (A,B,C)	1.640"	0.630"
VS438 (B)	1.435"	0.562"	VS303 (A,B,C)	1.480"	0.700"			
VS437 (A,B)	1.437"	0.500"	VS103 (A)	1.500"	1.020"			

VALVE STEM SEALS

Part Number	Valve Stem	Guide Diam.	Part Number	Valve Stem	Guide Diam.	Part Number	Valve Stem	Guide Diam.
VSV108	.342" (11/32")	.502"	VSV530	.342" (11/32")	.530"	S9	8mm	.500"
KG303	.342" (11/32")	.765"	KG317	.342" (11/32")	.700"	VSV802	.311" (5/16")	.531"
KG819	.342" (11/32")	.280"						


PUSHROD GUIDE PLATES

Part Number	Pushrod Diameter	Application	Part Number	Pushrod Diameter	Application
GP186	5/16"	Holden 6. 186,202	GP308	5/16"	Holden 308
GP350	5/16"	Chev 350 Stepped	GP351	5/16"	Ford 351C Stepped
GP302	5/16"	Ford 302W	GP304	5/16"	Holden EFI V8
GP455	7/16"	Chev Big Block			

VALVE STEM LASH CAPS (0.080" Thick)

Part Number	Dimensions	Application
34301	11/32" valve 0.343"	Holden, Chev SB, Ford 302-351

CROW CAMS DEGREE WHEELS

Part Number		Part Number	
DW1 8" Black Degree Wheel Center Hole Diameter: 19.5mm		DW2 11" Racer Degree Wheel Center Hole Diameter: 10mm	