TOYOTA

Application	RPM Range	Part No.	Adv. Duration				+	Valve Lift		LSA	Lash Las Intake Exh	Lash Exhaust	Lifters	Valve	Installed	Retainer	Locks	Stem Seal	Timing Kit	Pushrods	Rockers
			Intake	Exhaust	Intake	Exhaust	Intake	Exhaust Lon	Lon		Intake	Exhaust	LIIIGIS	Spring	Height	netalliel	LUCKS	Stelli Seal	Tilling Kit	Pusilious	HOURCIS
3SGE, 3SGTE TWI	N CAM USE ZDI	DP100 OIL AI	DDITIVE AN	ND QUALIT	Y MINERA	L ENGINE	OIL ONLY														
Mild performance cams	2200 - 5800	3481416 3481416	264	264	207	207	.345"	.345"													
Mild performance cams	2700 - 6700	3481587 3481587	268	268	219	219	.360"	.360"													
Hot street/race cams	2800 - 6800	3481407 3481407	270	270	227	227	.368"	.368"													
4A-GE 1600 TWIN	CAM USE ZDDP1	IOO OIL ADDIT	TIVE AND (QUALITY M	IINERAL E	NGINE OIL	ONLY	•													
Mild performance cams	2200 - 6200	271215 272215	277	277	218	218	.315"	.315"													
Mild performance cams	2700 - 6700	271152 272152	280	280	234	234	.334"	.334"													
Hot street/race cams	3200 - 7200	2711323 2721323	285	285	240	240	.330"	.330"													
4A-GE 20 VALVET	TWIN CAM (USE ZDDP100	OIL ADDI	TIVE AND	QUALITY N	MINERAL E	NGINE OIL	. ONLY							,						
Mild performance cams	2000 - 5600	274215 275215	277	277	218	218	.315"	.315"													
Mild performance cams	2500 - 5800	274152 275152	280	280	234	234	.334"	.334"													
Mild street performance cams	2800 - 6000	2741323 2751323	285	285	240	240	.330"	.330"													
Hot street/race cams	3500 - 7200	274859 275859	307	307	257	257	.388"	.388"													
2JZ-GTE USE ZDDP100 OIL	ADDITIVE AND QUALIT	Y MINERAL E	ENGINE OI	L ONLY																	
Mild performance cams	2300 - 6200	5411587 5421587	268	268	219	219	.360"	.360"													
Mild street performance cams	2800 - 6800	5411407 5421407	270	270	227	227	.368"	.368"													