



## CAMSHAFT SPECIFICATIONS

Part number: <b>15794</b>		Cam Type: <b>Solid flat tappet</b>	
Adv ground on Cam: <b>2°</b>		LSA: <b>107°</b>	ICL: <b>105°</b>
Inlet Lobe lift at TDC: <b>.128"</b>			ECL: <b>109°</b>
Valve Timing @ .050"	In opens: <b>28 BTDC</b>	Ex opens: <b>63 BBDC</b>	Duration: <b>265°</b>
	In closes: <b>58 ABDC</b>	Ex closes: <b>25 ATDC</b>	Duration: <b>268°</b>
Adv Valve Timing @ .006"	In opens: <b>48 BTDC</b>	Ex opens: <b>84 BBDC</b>	Duration: <b>305°</b>
	In closes: <b>78 ABDC</b>	Ex closes: <b>46 ATDC</b>	Duration: <b>310°</b>
In Lobe Lift (inch) <b>0.378</b>	Ex Lobe Lift: <b>0.377</b>	Rocker Ratio: <b>1.62</b>	
In Valve lift (inch) <b>0.612</b>	Ex Valve lift: <b>0.611</b>		
In Lash <b>.014"</b>	Ex Lash <b>.016"</b>		

These high performance components should be checked for suitability by the person installing them as engines of the same group can vary in valve length, spring installed height and collet grooves.  
**IT IS THE SOLE RESPONSIBILITY OF THE INSTALLER TO CHECK SUITABILITY.**