Crow Cams Australia Pty Ltd
1 Griffith Street, Knoxfield VIC 3180
Tel: 03 9357 0469 Email: info@crowcams.com.au

CAMSHAFT SPECIFICATIONS

Part number: 35613 **Cam Type:** Hydraulic flat tappet

Adv ground on Cam:	2°		LSA:	112°		ICL:	110°
Inlet Lobe lift at TDC:	.020"					ECL:	114°
Valve Timing	In opens:	-13 BTDC	Ex opens:	35 BBDC		Duration:	194°
@ .050"	In closes:	27 ABDC	Ex closes:	-13 ATDC		Duration:	202°
Adv Valve Timing	In opens:	20 BTDC	Ex opens:	68 BBDC		Duration:	260°
@ .006"	In closes:	60 ABDC	Ex closes:	20 ATDC		Duration:	267°
In Lobe Lift (inch)	0.260		Ex Lobe Lift:	0.272		Rocker Ratio:	1.5
In Valve lift (inch)	0.390		Ex Valve lift:	0.408			

These high performance components should be checked for suitability by the person installing them as engines of the same group can vary in valve length, spring installed height and collet grooves.
IT IS THE SOLE RESPONSIBILITY OF THE INSTALLER TO CHECK SUITABILITY.